

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace, without prejudice, all prior versions, and listings, of claims in the application.

Listing of Claims:

b1
Sub
c1
1 (Currently Amended) A method for controlling wheel brakes in an electrical braking system of a motor vehicle, comprising the steps of:

generating control driving signals for valve arrangements for a control of a braking pressure in a first group of the wheel brakes from a first power circuit and for a control of a braking pressure in a second group of the wheel brakes from a second power circuit that is independent of the first group of the wheel brakes; and

detecting a fault in an area of at least one of the valve arrangements, a pressure supply, and an electrical system of the electrical braking system, wherein:

when the fault affects those of the wheel brakes supplied by the first power circuit, the control driving signals for one of the valve arrangements are generated, a power for an activation of the one of the valve arrangements originating from the second power circuit, and a warning is generated to inform a driver of fault detection; and
in the fault condition of one of the wheel brakes, a speed of the motor vehicle is limited.

2. (Previously Presented) A method for controlling wheel brakes in an electrical braking system of a motor vehicle, comprising the steps of:

generating control driving signals for valve arrangements for a control of a braking pressure in one of the wheel brakes from a first power circuit, a braking pressure being provided by at least one of an accumulator and a pump; and

detecting a fault in an area of at least one of the valve arrangements, a

pressure supply, and an electrical system of the electrical braking system, wherein:

b1
cont
when the fault occurs in one of an accumulator circuit, a pump circuit, and the first power circuit, a valve is activated at a brake actuator of a front one of the wheel brakes, the valve isolating the pump circuit from the accumulator circuit.

c1
cont
3. (Previously Presented) The method according to claim 1, wherein:

when the fault condition occurs, the control driving signals are generated to actuate at least one of additional valve arrangements and existing valve arrangements via a redundant electrical control on the basis of the power of the second power circuit.

4. (Currently Amended) A method for controlling wheel brakes in an electrical braking system of a motor vehicle, comprising the steps of:

generating control driving signals for valve arrangements for a control of a braking pressure in a first group of the wheel brakes from a first power circuit and for a control of a braking pressure in a second group of the wheel brakes from a second power circuit that is independent of the first group of the wheel brakes; and

detecting a fault in an area of at least one of the valve arrangements, a pressure supply, and an electrical system of the electrical braking system, wherein:

when the fault affects those of the wheel brakes supplied by the first power circuit, the control driving signals for one of the valve arrangements are generated, a power for an activation of the one of the valve arrangements originating from the second power circuit; and

in a the fault condition of one of the wheel brakes, a speed of the motor vehicle is limited.

5. (Currently Amended) A method for controlling wheel brakes in an

electrical braking system of a motor vehicle, comprising the steps of:

generating control driving signals for valve arrangements for a control of a braking pressure in one of the wheel brakes from a first power circuit, a braking pressure being provided by at least one of an accumulator and a pump; and

detecting a fault in an area of at least one of the valve arrangements, a pressure supply, and an electrical system of the electrical braking system, wherein:

when the fault occurs in one of an accumulator circuit, a pump circuit, and the first power circuit, a valve is activated at a brake actuator of a front one of the wheel brakes, the valve isolating the pump circuit from the accumulator circuit; and

in a the fault condition of one of the wheel brakes, a speed of the motor vehicle is limited.

6. (Previously Presented) The method according to claim 1, wherein:

in a fault condition in an area of a front axle brake actuator, a braking pressure control occurs in front ones of the wheel brakes according to control driving signals generated from a control module assigned to one of rear ones of the wheel brakes.

7. (Previously Presented) The method according to claim 2, wherein:

in a fault condition in an area of a front axle brake actuator, a braking pressure control occurs in front ones of the wheel brakes according to control driving signals generated from a control module assigned to one of rear ones of the wheel brakes.

8. (Previously Presented) The method according to claim 1, wherein:

when the fault condition occurs, control driving signals of a control module of those of the wheel brakes corresponding to rear axle brakes are generated to activate additional valve arrangements via

which a braking pressure in those of the wheel brakes corresponding to front wheel brakes is set.

b1
cont
9. (Currently Amended) A computer program for causing a computing unit of a control unit to perform the steps of:

c1
cont
generating control driving signals for valve arrangements for a control of a braking pressure in a first group of wheel brakes from a first power circuit and for a control of a braking pressure in a second group of the wheel brakes from a second power circuit that is independent of the first group of the wheel brakes; and

detecting a fault in an area of at least one of the valve arrangements, a pressure supply, and an electrical system of an electrical braking system, wherein:

when the fault affects those of the wheel brakes supplied by the first power circuit, the control driving signals for one of the valve arrangements are generated, a power for an activation of the one of the valve arrangements originating from the second power circuit, and a warning is generated to inform a driver of fault detection; and

in the fault condition of one of the wheel brakes, a speed of the motor vehicle is limited.

10. (New) A method for controlling wheel brakes in an electrical braking system of a motor vehicle, comprising the steps of:

generating control driving signals for valve arrangements for a control of a braking pressure in a first group of the wheel brakes from a first electrical power circuit and for a control of a braking pressure in a second group of the wheel brakes from a second electrical power circuit that is independent of the first group of the wheel brakes; and

detecting a fault in an area of at least one of the valve arrangements, a pressure supply, and an electrical system of the electrical braking system, wherein:

b1
cont

C1
cont

when the fault affects those of the wheel brakes supplied by the first electrical power circuit, the control driving signals for one of the valve arrangements are generated, a power for an activation of the one of the valve arrangements originating from the second electrical power circuit, and a warning is generated to inform a driver of fault detection.
